



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

FOOD MACHINES - AMPERE RATINGS



FOOD MACHINES - AMPERE RATINGS

MACHINE	MODEL	H.P.	1 PHASE			3 PHASE		
			115V	200V	230V	200V	230V	460V
Choppers	4812	½	7.0	—	3.5	—	—	—
	4822	1½	12.0	—	6.0	3.4	3.4	1.7
	4732A	3	—	19.5	18.0	8.6	8.1	4.0
	4146	5	—	—	—	20.6	19.5	9.8
Cutter/Mixers	HCM450	5	—	—	—	23.5	20.0	10.0
Fat Tester	F101	—	4.5	—	2.2	—	—	—
Food Cutters	84145	½	9.5	—	4.7	3.6	—	—
	84186	1	13.0	—	6.5	3.8	—	1.8
Food Processors	FP41	¾	⁵ 10.4	—	—	—	—	—
	HCM61	1½	⁵ 15.4	—	—	—	—	—
	HCM62	2	—	—	—	³ 5.1	³ 5.1	—
	FP100	½	⁵ 3.5	—	—	—	—	—
	FP150	½	⁵ 4.8	—	—	—	—	—
	FP250	¾	⁵ 7.0	—	—	—	—	—
	FP300	1	⁵ 10.0	—	—	—	—	—
	FP350	1	⁵ 10.0	—	—	—	—	—
Mixers	FP400	2	—	—	—	³ 7.5	³ 7.5	—
	N50	⅙	3.2	—	1.4	—	—	—
	HL120	½	8.0	5.0 (200-240)		—	—	—
	HL200	½	8.0	5.0 (200-240)		—	—	—
	HL300	¾	9.5	5.7 (200-240)		2.8		1.4
	HL400	1½	—	9.3 (200-240)		5.6		2.4
	HL600	2.7	—	16.0 (200-240)		8.0 (200-240)		4.0 (380-460)
	HL662	2.7	—	16.0 (200-240)		8.0 (200-240)		4.0 (380-460)
Mixer Grinders	HL800	3	—	—	—	11.0		5.2
	HL1400	5	—	—	—	14.8		6.8
	4246-S	5/1	—	³ 26.0	³ 26.0	¹ 16.0	² 15.0	⁷ 7.5
	4246-HD	7.5/1	—	—	—	¹ 30.0	² 30.0	⁷ 15.0
	MG1532	5/1	—	³ 26.0	³ 26.0	—	—	—
Peelers	MG1532	7.5/1	—	—	—	¹ 30.0	² 30.0	⁷ 15.0
	MG2032	7.5/1	—	—	—	¹ 30.0	² 30.0	⁷ 15.0
	6115	⅓	7.2	—	3.6	—	—	—
	6430	¾	13.0	⁶ 6.5	⁶ 6.5	⁶ 3.2	⁶ 3.2	1.6
Power Drive	6460	1	16.6	⁶ 8.3	⁶ 8.3	⁶ 3.8	⁶ 3.8	1.9
	6460M	1	16.6	—	—	³ 3.8	³ 3.8	1.9
Power Drive	PD-35	½	9.7	—	—	—	—	—
	PD-70	½	7.3	—	—	—	—	—

NOTE: ¹ = 208 Volt ² = 240 Volt ³ = 208-240 Volt ⁴ = 220 Volt ⁵ = 120 Volt ⁶ = 200-230 Volt ⁷ = 480 Volt

FOOD MACHINES - AMPERE RATINGS



701 S Ridge Avenue, Troy, OH 45374
1-888-4HOBART • www.hobartcorp.com

MACHINE	MODEL	H.P.	1 PHASE			3 PHASE		
			115V	200V	230V	200V	230V	460V
Salad Dryers	SDPE	¼	2.5	—	1.3	—	—	—
	SDPS	¼	2.5	—	1.3	—	—	—
Saws	6801, 6614	3	—	³ 16.5	³ 16.5	⁶ 9.3	⁶ 8.2	4.1
Slicers	610	⅓	⁵ 2.0	—	—	—	—	—
	Edge™	⅓	⁵ 3.5	—	—	—	—	—
	2612	½	⁵ 5.0	—	² 2.5	—	—	—
	2712	½	⁵ 6.0	—	² 3.0	—	—	—
	2812	½	⁵ 5.0	—	—	—	—	—
	2912	½	⁵ 6.0	—	—	—	—	—
	2812PS	½	⁵ 5.0	—	—	—	—	—
	2912PS	½	⁵ 6.0	—	—	—	—	—
	2912B	½	⁵ 6.0	—	—	—	—	—
	2612PHS	½	⁵ 5.0	—	² 2.5	—	—	—
	2712PHS	½	⁵ 6.0	—	² 3.0	—	—	—
	3613	½	⁵ 5.0	—	⁶ 2.5	—	—	—
	3613N	½	⁵ 5.0	—	⁶ 2.5	—	—	—
	3713	½	⁵ 6.25	—	⁶ 3.75	—	—	—
	3713N	½	⁵ 6.25	—	⁶ 3.75	—	—	—
	3813	½	⁵ 5.0	—	⁶ 2.5	—	—	—
	3813N	½	⁵ 5.0	—	⁶ 2.5	—	—	—
	3913	½	⁵ 6.25	—	⁶ 3.75	—	—	—
3913N	½	⁵ 6.25	—	⁶ 3.75	—	—	—	
Spiral Mixers	HSL180	8.5	—	—	—	26.1 (200-220)	—	—
	HSL220	8.5	—	—	—	32.8 (200-220)	—	—
Tenderizer	403	½	8.1	—	—	—	—	—

NOTE: ¹ = 208 Volt ² = 240 Volt ³ = 208-240 Volt ⁴ = 220 Volt ⁵ = 120 Volt ⁶ = 200-230 Volt ⁷ = 480 Volt

As continued product improvement is a policy of Hobart, specifications are subject to change without notice.